



120' x 120' Volleyball Facility



65' x 130' Futsal® Facility

KEY BENEFITS

Performance: Play Better & Faster!

The ShockTower® understructure provides unsurpassed ball performance and play. Engineered to withstand competition at the highest levels.

Safety: Play Longer!

Patented ReactivePlay® technology gives an added level of "cush" to reduce impact on joints and limbs, letting you play longer today and for years to come.

Functionality: Play Now!

BounceBack® ShockTower Sports Surfacing installs easily. Each panel weighs much less than standard rubber flooring. Use it to upgrade your old gym in as little as one day.

SYSTEM FEATURES

Sixteen individual contact points ensure a consistent playing surface and excellent coefficient of friction to keep the surface in place.



The patented "resilient shock" technology was designed with performance and safety in mind. The built-in shock deflection offers exceptional impact control and provides excellent rolling load support.

SPECS

Solid Top Design (12"x12"x7/8")
High Impact Copolymer Suspended Flooring
16 Individual Impact Zones
Compressible shock design, (11/16" x 7/8" O.D.), 0.1 oz.
Weight: 22 oz. (635.02g)
Friction (ASTM C 1028): Dry-0.74, Wet-0.53
Rolling Load (DIN 18032-02): Pass
Force Reduction (DIN 18032-02): 44%
Standard Deformation (DIN 18032-02): 0.9mm
Ball Rebound (DIN 18032-02): 98%
Load Bearing Capacity (DIN 18032-02): >200 PSI
Flatness: 0.0mm
Lateral Movement: 0.00" – 0.065"
Noise Reduction Coefficient (ASTM C 423): 5-10%
For Architectural Specifications please visit our website: www.snapsports.com

SnapSports is a FIBA Associate Manufacturer for Indoor BounceBack ShockTower

APPLICATIONS

Schools
Church Family Life Centers
Recreation Centers
Multi-Activity Centers
Sports Camp Facilities
Rehab Clinics and Hospitals
Military
Sports Training Facilities

Aerobics
Dance
Pilates
Yoga
Martial Arts
Display
Events
Home Gyms

Private Athletic Clubs For:
Basketball
Volleyball
Futsal®
Team Handball
Raquetball & Squash
Badminton

► **SNAPSPORTS.COM**

☎ **800.664.DUNK**
(3865)